



DOUGLAS INDUSTRIES, INC.  
 3441 S 11TH AVE.  
 ELDRIDGE, IA 52748  
 TOLL FREE: 1-800-553-8907  
 www.douglas-sports.com

SELECT DESIRED COLOR:


- DARK GREEN
- BLACK

SELECT DESIRED PANEL HEIGHT:  
 (MAX 60'-0" LENGTH, RECOMMENDED)

- 6'-0"
- 9'-0"
- SPECIFY \_\_\_\_\_

SELECT DESIRED AIR VENT OPTION:

- AVR AIR VENTS (#21002)



**SPECIFICATIONS:**


**FABRIC:** 100% POLYPROPYLENE, OPEN MESH - 28 X 14 LENO WEAVE  
**WINDBREAK:** OPEN 85%  
**WEIGHT PER SQUARE YARD:** 7 OZ.  
**TENSILE STRENGTH:** 380 X 185  
**WARRANTY:** 4 YEAR LIMITED

**SUGGESTIONS FOR MEASURING AND ORDERING WINDSCREENS**

- MEASURE ALL FENCES TENSION BAR TO TENSIONS BAR. DON'T INCLUDE THE END POSTS IN THE MEASUREMENT, AS WINDSCREENS SHOULD COVER ONLY THE FENCE MESH. MEASURE DOORS AND TRANSOMS THE SAME WAY. SEND A SKETCH WITH YOUR MEASUREMENTS.
- ALWAYS MEASURE AT THE SITE WHENEVER POSSIBLE RATHER THAN FROM DRAWINGS/BLEUPRINTS.
- RUN MEASURING TAPE ALONG THE GROUND. SLACK OCCURS IF THE TAPE IS RUN ALONG THE FENCE.
- SEND US EXACT MEASUREMENTS OF ALL FENCES AND DOORS IN FEET AND INCHES.
- ROUND DOWN TO THE NEAREST INCH FOR EACH AREA; NO PARTIAL INCHES.
- FOR EASE OF HANDLING, ORDER PANELS 60 FEET IN LENGTH OR SHORTER.
- AIR VENTS ARE RECOMMENDED ON ALL PANELS OVER 6' HIGH AND ALSO IN AREAS WITH HIGH WINDS.
- WE RECOMMEND LABELING PANELS FOR BETTER ORAGANIZATION UPON INSTALLATION.

**NOTES:**

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT [www.CADdetails.com/info](http://www.CADdetails.com/info) AND ENTER REFERENCE NUMBER 2763-064.



**WINDSCREENS**

DOUGLAS® POLY-PRO™ PLUS PREMIUM (OMP - OPEN MESH)